



SYNESSO

## Synesso Sabre Specifications

<b><u>Model</u></b>	<b><u>2 Group</u></b>	<b><u>3 Group</u></b>
Voltage, Single Phase	220	220
Hertz	50 / 60	50 / 60
Amps - max draw	28	36
<b>Brew &amp; Steam Specifications:</b>		
Watts per Element, Steam Tank	2000 x 2	2500 x 2
Total Steam Element Wattage	4000	5000
Steam Tank Capacity (Liters)	7.7	12.3
Watts per Element, Brew Tank	700 x 2	700 x 3
Brew Tank Capacities (Liters)	1.9 x 2	1.9 x 3
<b>Machine Dimensions:</b>		
	<b>Inches / mm</b>	<b>Inches / mm</b>
Height (Steam Wand 21", Handle 20.5")	18" / 457	18" / 457
Width (Steam Handle to Handle add 3")	29" / 736	40" / 1016
Depth	23" / 584	23" / 584
<b>Weights &amp; Dimensions:</b>		
	<b>Lbs / Kgs</b>	<b>Lbs / Kgs</b>
Machine Weight, Empty	154 / 70	190 / 86
Machine Weight, Full of Water	173 / 77	215 / 98
Shipping Weight (approximate)	225 / 103	270 / 123
Boxed Dimensions: L" x W" x H"	41" x 32" x 31"	49" x 32" x 31"
Boxed Dimensions: L x W x H m/m	1042x762x787	1245x813x787
<b>Plumbing (Compression)</b>	3/8" OD	3/8" OD

- C-Tick Models available for Australian and New Zealand markets
- CE Certified for safety

